

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICANT: Serra Obiol

SERIAL NO.: 09/463,914

ART UNIT: 3724

FILED: February 1, 2000

EXAMINER: Florez Sanchez, O

TITLE: SYSTEM FOR FIXING ROTARY CUTTING DIES IN MACHINES FOR DIE CUTTING  
LAMINAR MATERIAL

CERTIFICATE OF MAILING UNDER 37 CFR 1.8(a)

Assistant Commissioner for Patents  
Washington, D.C. 20231

Sir:

I hereby certify that the attached correspondence comprising:

AMENDMENT "A"


is being deposited with the United States Postal Service with sufficient postage as first class mail  
in an envelope addressed to:

Commissioner of Patents and Trademarks  
Washington, D.C. 20231

on February 21, 2001.

Respectfully submitted,

2-21-01  
Date

  
\_\_\_\_\_  
John S. Egbert  
Reg. No. 30,627  
Attorney for Applicant  
Harrison & Egbert  
412 Main Street  
7<sup>th</sup> Floor  
Houston, Texas 77002  
(713)224-8080

RECEIVED  
MAR - 1 2001  
TECHNOLOGY CENTER R3700



GP/3724 2-EC  
5/B

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICANT: Serra Obiol

SERIAL NO.: 09/463,914

ART UNIT: 3724

FILED: February 1, 2000

EXAMINER: Florez Sanchez, O

TITLE: SYSTEM FOR FIXING ROTARY CUTTING DIES IN MACHINES FOR DIE CUTTING LAMINAR MATERIAL

AMENDMENT "A"

Assistant Commissioner for Patents  
Washington, D.C. 20231  
Box Non-Fee Amendment

Sir:

In response to the Official Action of December 8, 2000, a response being due by March 8, 2001, please amend the above-identified application as follows:

IN THE SPECIFICATION

Please cancel Claims 1-10 and insert Claims 11-21 therefor as follows:

11. An apparatus for die cutting laminar material comprising:
- a cutting die support cylinder;
  - a cutting die; and
  - a fixing means for securing said cutting die to said cutting die support cylinder, said fixing means comprising:
    - a bolt; and
    - a working device housed within a hollow body affixed to said cutting die support cylinder, said working device operatively connected to said bolt so as to resiliently move said bolt from a retracted position to an extended position in which said bolt has a head extending outwardly

RECEIVED  
MAR - 1 2001  
TECHNOLOGY CENTER R3700

B1